1.5 Gal. Oil-Free Fully Shrouded Air Compressor

PORTER✦CABLE Durable oil-free pump for long life and no maintenance. Motor starts easily in cold weather or with extension cord.

- 20 lbs. for easy portability
- Low noise at 79 dBA for a quieter working environment
- Fully enclosed design provides protection from hot or moving parts

Air delivery (scfm) 3.0 @ 40 psi/ 2.0 @90 psi. Weight 20 lbs.

Includes 25' nylon coil hose, 2 tapered nozzles, inflation needle, 1/4" tire chuck, hose adapter, 2-piece high flow inflator/deflator kit & teflon tape.

Stk.	Mfr.	Volts	HP	Max. Pressure	Tank Capacity	Price
636778	CMB15	120	.75	150 psi	1.5 gal.	**$176.00**

2 Gallon Air Compressor

Campbell Hausfeld User-friendly control panel provides easy monitoring of gauges. High-quality, 1-piece manifold. Cooler running motor with automatic shut-off. Sturdy retractable handle allows comfortable handling. Accessory storage bin. 1-yr. mfr.'s warranty.

Air delivery (scfm) 1.0 @ 40 psi & 0.7 @ 90 psi. Size 16.9"L x 10.2"W x 15.4"H. Weight 20 lbs.

Includes air chuck, 2 inflation nozzles, needle adapter, inflation needle & 25' recoil hose.

Stk.	Mfr.	Volts	HP	Max. Pressure	Tank Capacity	Price
291131	FP2048	120	1/3	100 psi	2 gal.	**$137.00**

0.8 HP Air Compressor

PORTER✦CABLE Low amp 120V motor starts easily in cold weather or with extension cord. 6 gal. pancake style tank for stability, includes water drain valve and rubber feet. Higher pressure for longer air tool performance.

- Oil-free, no maintenance pump
- 2.6 scfm @ 90 psi for fast recovery time
- Upgraded shroud, handle & console cover protect vital components
- 2 regulated air couplers for 2 users
- Hi-flo regulator

Air delivery (scfm) 3.5 @ 40 psi & 2.6 @ 90 psi. Weight 34 lbs.

Includes 13 pc. accessory kit (25' x 1/4" PVC air hose w/coupler & plug, tire chuck w/plug, blo-gun w/plug, tire gauge, OSHA safety nozzle w/4 inflator adapters), on-board cord wrap & manual.

Stk.	Mfr.	Volts	HP	Max. Pressure	Tank Capacity	Price
636776	C2002-WK	120	.8	150 psi	6 gal.	**$279.00**

Heavy Duty Trim Compressor

DEWALT Compact, portable and can be operated/ stored in either the vertical or horizontal position. Roll cage design creates a convenient and comfortable handle for transportation, storage, and protection. Shroud has a cord wrap for easy storage and the tank has a ball drain valve for quick and thorough tank draining. Durable, oil-free pump provides maintenance-free operation.

- 12 amp motor provides easy start-up and reduces breaker tripping
- Dual quick couplers to easily support 2 nailers
- 71.5 dB operating noise level
- High-flow regulator for increased performance

Air delivery (scfm) 4.0 scfm @ 40 psi & 3.0 scfm @ 90 psi.
Tool size 20.5"L x 16.75"W x 12.5"H. Weight 36 lbs.

Includes 2 universal couplers.

Stk.	Mfr.	Volts	HP	Max. Pressure	Tank Capacity	Price
243425	DWFP55130	120	1.1	200 psi	2.5 gal.	**$343.00**

1 HP Air Compressor

Senco 4 Amp compressor with a direct-drive induction motor for finish and trim work, plus crafts. Ultra-quiet, electric operation. Lube-free. Easy-read tank and pressure gauges. Lightweight aluminum tank and soft-grip handle. 1-yr. mfr.'s warranty.

Air delivery (scfm) 1 @ 40 psi & 0.7 @ 90 psi. Size 14"L x 12.5"W x 10"H. Weight 20 lbs.

Includes regulator, pressure gauges, 1/4" universal coupler & air filter.

Stk.	Mfr.	Volts	HP	Max. Pressure	Tank Capacity	Price
291536	PC1010	110	1	125 psi	1 gal.	**$207.00**

5 & 5.5 HP Air Compressors

Campbell Hausfeld Maintenance free oil-free direct drive workhorse offers easy-to-operate controls with descriptive icons.

- Oversized, easy-reference gauges
- Hot moving parts covered by durable shroud
- Storage for couplers, plugs, tape
- UL listed

Air delivery (scfm) 6.5 @ 40 psi & 51 @ 90 psi. ***Air hoses sold separately.***

Stk.	Mfr.	Volts	HP	Max. Pressure	Tank Capacity	Weight	Price
291096	WL6501	120	5	125 psi	13 gal.	76 lbs.	**$498.00**
291095	WL6502	120	5.5	125 psi	20 gal.	89 lbs.	**$520.00**

1.1 HP Air Compressor

DEWALT 2-Pole, 3,400 rpm direct drive, low amp induction motor with dual soft start valves. Oil-lubricated pump w/cast iron cylinder for durability. High-flow regulator increases performance. Hand-carry 4 gal. twin stack tank. Rapid recovery operating at 90 psi.

Air delivery (scfm) 5.4 @ 40 psi & 4.6 @ 90 psi. Weight 56.5 lbs.

Includes compressor oil.

Stk.	Mfr.	Volts	HP	Max. Pressure	Tank Capacity	Price
242870	D55153	120	1.1	125 psi	4 gal.	**$384.00**

1.3 HP Air Compressor

Campbell Hausfeld Low amp motor for high-quality performance with fewer tripped circuit breakers.

- Oil-lubricated pump, cast iron single cylinder
- Durable, safe ASME code tank
- Oil sight glass for visual monitoring of oil level

Air delivery (scfm) 4.5 @ 40 psi & 3.7 @ 90 psi. Weight 75 lbs.

Air hoses sold separately.

Stk.	Mfr.	HP	Max. Pressure	Tank Capacity	Price
291119	HL5401	1.3	125 psi	8 gal.	**$275.00**

Proudly serving Educators with Top Name Brand Tools &
Outstanding Customer Service for over 100 years!